



PRESSMATIC URINAL PUSH COCK

Celebrate both hygiene and
eco-friendliness.

Pressmatic Urinal Pushcock

Watertec's Pressmatic Urinal Pushcock is constructed to control the flow of water in urinals.

The press button has been scientifically tested to ensure durability and consistency.

This water efficient product saves water, conveniently!

Pressmatic Urinal Pushcock - Technical Specifications

S. No.	Parameter	Specifications
1	Application	Used for urinal toilets
2	Number of Water Outlets	One
3	Water Connection	½" BSP
4	Material	High grade engineering polymer. Push button made of brass alloy CP version. Outlet flexible extension hose made of brass alloy CP version
5	Finish	Smooth internals provides non-rusted / non-clogging water flow. Heavy & robust body with impeccable surface finish and durable in moistures condition
6	Installation Type	Wall mount - ½" BSP outlet directly connected with plumbing line
7	Flow Rate	Flow @ 3 Bar - Single Press - 0.8 to 1.5 Ltr - Timing – 10 to 11 Secs
8	Actuation Mechanism	Auto Closing - High quality time cartridge used are tested 2 lakh times to ensure a longer and trouble-free operating life. The Push Cock works smoothly on various pressure conditions (1 to 6bar).
9	Control Cock	Control the water flow needed. It restricts the water flow up to 1.3* Ltr per min at 3 bar pressure



Eco-friendly



Durable



Consistent

WATERTEC®

Gopal Bagh #1060, Avinashi Road, Coimbatore - 641 018, India.

Ph: 0422 2245295 | E-mail: marketing@watertecindia.com

Toll-free: 1800 121 2191



www.watertecindia.com

